

SHIFT CONTROL APPARATUS AND SHIFT CONTROL METHOD FOR A VEHICULAR AUTOMATIC TRANSMISSION

INCORPORATION BY REFERENCE

5 **[0001]** The disclosures of Japanese Patent Application No. 2002-350526
filed on December 2, 2002, including the specification, drawings and abstract is
incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

10 **[0002]** The invention relates to a shift control apparatus and shift control
method for a vehicular automatic transmission, which enables suppression of a drop
in rotational speed of an input shaft which occurs during a clutch-to-clutch downshift
executed while a vehicle is decelerating.

2. Description of the Related Art

15 **[0003]** A shift control apparatus for a vehicular automatic transmission is
known which, when executing a clutch-to-clutch downshift, executes shift hydraulic
pressure control so as to reduce an apply pressure of a hydraulic friction device to be
released, which was applied in order to achieve a predetermined speed before the
downshift, while increasing an apply pressure of a hydraulic friction device to be
20 applied in order to achieve a predetermined speed after the downshift. According to
JP(A) 11-287318, for example, during the clutch-to-clutch downshift, feedback
control is performed on the apply pressure of the hydraulic friction device to be
applied so that a transmitted torque capacity of the hydraulic friction device to be
applied becomes constant, i.e., so that a rotational speed of an input shaft of the
25 automatic transmission increases at a constant rate.

[0004] In the aforementioned shift control apparatus for a vehicular
automatic transmission, the engine speed drops during the clutch-to-clutch downshift
when the vehicle is decelerating, and then increases again when the hydraulic friction
device to be applied is applied. This combination of a drop followed by an increase in
30 engine speed results in shift shock or a delay in the shift time. Also, fuel efficiency
may be reduced if the drop in engine speed is large enough to require that the fuel
supply be restarted.

[0005] In comparison, it is conceivable to automatically suppress the drop
in engine speed during the clutch-to-clutch downshift while the vehicle is

decelerating, and appropriately reduce or eliminate shift shock or a delay in shift time caused by that drop. It is also possible to appropriately reduce the adverse effect on fuel efficiency caused by fuel being supplied to the engine again due to a further drop in engine speed. However, doing so may result in shift shock occurring when there is
5 little or no drop in engine speed.

SUMMARY OF THE INVENTION

[0006] In view of the foregoing problems, this invention thus provides a shift control apparatus and shift control method for a vehicular automatic
10 transmission, which automatically suppresses a drop in engine speed during a clutch-to-clutch downshift executed while a vehicle is decelerating, appropriately reduces or eliminates shift shock or a delay in shift time caused by that drop in engine speed, and appropriately suppresses a reduction in fuel efficiency due to the fuel supply to the engine being restarted due to that drop in engine speed.

15 [0007] One aspect of the invention relates to a shift control apparatus for a vehicular automatic transmission which includes i) a fuel cut apparatus which performs a fuel cut in which a supply of fuel to an engine is cut off when an engine speed exceeds a predetermined value during deceleration of a vehicle, ii) an automatic transmission in which a gearshift is achieved with a clutch-to-clutch downshift in
20 which a hydraulic friction device to be released is released and a hydraulic friction device to be applied is applied, and iii) a controller which corrects, through learning control, an apply pressure of at least one of the hydraulic friction devices to be operated for the clutch-to-clutch downshift such that an amount of drop in a rotational speed of an input shaft of the automatic transmission increases when that amount of
25 drop is less than a predetermined value during the clutch-to-clutch downshift.

[0008] Also, another aspect of the invention relates to a shift control method for a vehicular automatic transmission which includes a fuel cut apparatus which performs a fuel cut in which a supply of fuel to an engine is cut off when an engine speed exceeds a predetermined value during deceleration of a vehicle, and an
30 automatic transmission in which a gearshift is achieved with a clutch-to-clutch downshift in which a hydraulic friction device to be released is released and a hydraulic friction device to be applied is applied. According to this shift control method, an apply pressure of at least one of the hydraulic friction devices to be operated for the clutch-to-clutch downshift is corrected through learning control such

that an amount of drop in a rotational speed of an input shaft of the automatic transmission increases when that amount of drop is less than a predetermined value during the clutch-to-clutch downshift.

5 [0009] According to the shift control apparatus and shift control method for a vehicular automatic transmission as described above, the apply pressure of the at least one of the hydraulic friction devices to be operated for the clutch-to-clutch downshift is corrected through learning control such that the amount of drop in the rotational speed of the input shaft of the automatic transmission increases when the degree of overlap between the release of the hydraulic friction device to be released and the application of the hydraulic friction device to be applied is large and the
10 amount of drop in the rotational speed of the input shaft of the automatic transmission is less than the predetermined value during the clutch-to-clutch downshift. As a result, shift shock caused by the large degree of overlap between the release of the hydraulic friction device to be released and the application of the hydraulic friction
15 device to be applied is able to be appropriately reduced or eliminated.

BRIEF DESCRIPTION OF THE DRAWINGS

 [0010] The above-mentioned embodiment and other embodiments, objects, features, advantages, technical and industrial significance of this invention
20 will be better understood by reading the following detailed description of the preferred embodiments of the invention, when considered in connection with the accompanying drawings, in which:

 FIG. 1 is a skeleton view illustrating a transverse-mounted vehicular driving apparatus for an FF vehicle to which a shift control apparatus
25 according to one exemplary embodiment of the invention is applied;

 FIG. 2 is a clutch and brake application chart showing various application and release combinations of clutches and brakes to achieve specific speeds in the automatic transmission shown in FIG. 1;

 FIG. 3 is a block diagram of a control system, which shows the input and output to and from an ECU provided in the vehicle according to the first
30 exemplary embodiment shown in FIG. 1;

 FIG. 4 is a view showing one example of a shift pattern of a shift lever shown in FIG. 3;

FIG. 5 is a graph showing one example of the relationship between an accelerator pedal operation amount A_{CC} and a throttle valve opening amount θ_{TH} used in throttle control performed by the ECU shown in FIG. 3;

5 FIG. 6 is a view showing a shift diagram (i.e., shift map) used in shift control of the automatic transmission performed by the ECU shown in FIG. 3;

FIG. 7 is a diagram illustrating main portions of a hydraulic pressure control circuit shown in FIG. 3;

10 FIG. 8 is a functional block diagram illustrating a major part of a control function of the ECU shown in FIG. 3, i.e., a shift control operation of the automatic transmission;

FIG. 9 is a time chart showing a major part of the control function of the ECU shown in FIG. 3, i.e., a basic control operation for a clutch-to-clutch downshift of the automatic transmission;

15 FIG. 10 is a flowchart of a main routine for illustrating a learning correction routine of a time until the start of sweep control of a hydraulic friction device to be released in a major part of the control function of the ECU shown in FIG. 3, i.e., in the shift control operation of the automatic transmission during a downshift of the automatic transmission while the vehicle is decelerating;

20 FIG. 11 is a flowchart of a learning correction value calculating routine which is a subroutine in the routine shown in FIG. 10;

FIG. 12 is a flowchart of a neutral avoidance learning routine which is a subroutine in the routine shown in FIG. 11;

FIG. 13 is a flowchart of a tie-up avoidance learning routine which is a subroutine in the routine shown in FIG. 11;

25 FIG. 14 is a time chart illustrating a case in which a normal learning routine or a high speed learning routine for a neutral tendency is executed in a major part of the control function of the ECU shown in FIG. 3, i.e., in the shift control operation of the automatic transmission during a downshift while the vehicle is decelerating;

30 FIG. 15 is a time chart illustrating a case in which an emergency learning routine for the neutral tendency is executed in a major part of the control function of the ECU shown in FIG. 3, i.e., in the shift control operation of the automatic transmission during a downshift while the vehicle is decelerating; and

FIG. 16 is a time chart illustrating a case in which an emergency learning routine for tie-up is executed in a major part of the control function of the ECU shown in FIG. 3, i.e., in the shift control operation of the automatic transmission during a downshift while the vehicle is decelerating.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0011] In the following description and the accompanying drawings, the present invention will be described in more detail in terms of exemplary embodiments.

10 **[0012]** FIG. 1 is a skeleton view of a transverse-mounted vehicular driving apparatus for a vehicle such as a FF (front engine, front drive) vehicle. Output from an engine 10, which is an internal combustion engine such as a gasoline engine, is transmitted to driven wheels (front wheels), not shown, via power transmitting apparatuses such as a torque converter 12, an automatic transmission 14, and a differential gear unit 16. The torque converter 12 includes a pump impeller 20 which is connected to a crankshaft 18 of the engine 10, a turbine impeller 24 which is connected to an input shaft 22 of the automatic transmission 14, a stator 30 which is fixed to a housing 28, which is a non-rotatable member, via a one-way clutch 26, and a lockup clutch 32 that directly connects the crankshaft 18 with the input shaft 22 via a damper, not shown. A mechanical oil pump 21 such as a gear pump is connected to the pump impeller 20. This oil pump 21 is driven together with the pump impeller 20 by the engine 10 so as to generate hydraulic pressure used for shifting and lubrication and the like. The engine 10 is a driving power source for running a vehicle. The torque converter 12 is a fluid coupling which is capable of boosting torque.

25 **[0013]** The automatic transmission 14 includes a first planetary gearset 40, a second planetary gearset 42, and a third planetary gearset 46, all of which are of the single pinion type, and an output gear 48. The first planetary gearset 40 and second planetary gearset 42 are both provided on the same axis as the input shaft 22, with a carrier of the first planetary gearset 40 coupled to a ring gear of the second planetary gearset 42 and a carrier of the second planetary gearset 42 coupled to a ring gear of the first planetary gearset 40, such that the first planetary gearset 40 and second planetary gearset 42 together form a carrier-ring, carrier-ring (CR-CR) coupled planetary gearset. The third planetary gearset 46 is provided on the same axis as a countershaft 44 which is parallel with the input shaft 22. The output gear 48 is fixed

30

to one end of the countershaft 44 and is meshed with the differential gear unit 16. The structural elements of the first planetary gearset 40, the second planetary gearset 42, and the third planetary gearset 46, i.e., a sun gear, a ring gear, and a carrier that rotatably supports planet gears that mesh with the sun gear and ring gear, can either be
 5 selectively coupled together by four clutches C0, C1, C2, and C3, or selectively coupled to the housing 28, which is a non-rotatable member, by three brakes B1, B2, and B3. Further, two one-way clutches F1 and F2 enable a carrier K2 and a sun gear S3, respectively, to either rotate in a given direction with respect to the housing 28, or engage with the housing 28. Because the differential gear unit 16 is symmetrical with
 10 respect to the axis of the drive axles, the bottom half thereof will be omitted.

[0014] The set of the first planetary gearset 40 and second planetary gearset 42 on the same axis as the input shaft 22, together with the clutches C0, C1, C2, the brakes B1 and B2, and the one-way clutch F1 make up a primary transmitting portion MG capable of four forward speeds and one reverse speed. The third
 15 planetary gearset 46 on the same axis as the countershaft 44, together with the clutch C3, the brake B3, and the one-way clutch F2 make up a secondary transmitting portion, i.e., an under drive portion U/D. In the primary transmitting portion MG, the input shaft 22 is coupled to i) the carrier K2 of the second planetary gearset 42 via the clutch C0, ii) a sun gear S1 of the first planetary gearset 40 via the clutch C1, and iii)
 20 a sun gear S2 of the second planetary gearset 42 via the clutch C2. A ring gear R1 of the first planetary gearset 40 is connected to the carrier K2 of the second planetary gearset 42, and a ring gear R2 of the second planetary gearset 42 is connected to a carrier K1 of the first planetary gearset 40. The sun gear S2 of the second planetary gearset 42 is coupled to the housing 28 via the brake B1. The ring gear R1 of the first
 25 planetary gearset 40 is coupled to the housing 28 via the brake B2. The one-way clutch F1 is provided between the carrier K2 of the second planetary gearset 42 and the housing 28. A first counter gear G1, which is fixed to the carrier K1 of the first planetary gearset 40, is in mesh with a second counter gear G2, which is fixed to a ring gear R3 of the third planetary gearset 46. In the underdrive portion U/D, a carrier
 30 K3 and the sun gear S3 of the third planetary gearset 46 are coupled together via the clutch C3. Also in the underdrive portion U/D, the brake B3 and the one-way clutch F2 are provided in parallel between the sun gear S3 and the housing 28.

[0015] The clutches C0, C1, C2, and C3 and the brakes B1, B2, B3 (hereinafter simply referred to as “clutches C” and brakes B”, respectively, when not

specified further) are hydraulic friction devices, the clutches C being, for example, multi-disc clutches and the brakes B being multi-disc clutches or band brakes or the like which are applied by hydraulic actuators. These clutches C and brakes B are switched between an applied state and a released state, as shown in FIG. 2, for example, by switching solenoids S1 to S5 and linear solenoid valves SL1, SL2, and SLU of a hydraulic pressure control circuit 98 (see FIG. 3) between an energized state and a de-energized state, or by switching a hydraulic circuit using a manual valve, not shown. Each speed, i.e., five forward speeds, one reverse speed, and a neutral speed, is achieved according to a position of a shift lever 72 (see FIG. 3). The denotations "1st" to "5th" in FIG. 2 denote the first forward speed to the fifth forward speed, respectively. A single circle indicates an applied state of the clutches C and brakes B. An "X" indicates a released state of the clutches C and brakes B. A triangle indicates an applied state of the clutches C and brakes B only during driving. The shift lever 72 is operated in a shift pattern which includes a park position "P", a reverse drive position "R", a neutral position "N", and forward drive positions "D", "4", "3", "2", and "L", as shown in FIG. 4, for example. When the shift lever 72 is in the "P" or the "N" position, the transmission is in a neutral speed, i.e., a non-driving speed in which the transmission of power to the wheels is interrupted. When the shift lever 72 is in the "P" position, the driven wheels are mechanically prevented from rotating by a mechanical parking mechanism, not shown. Also, the five forward speeds and the one reverse speed achieved when the shift lever 72 is in any one of the forward drive positions, such as the "D" position, or the "R" position, respectively, correspond to driving speeds. Further, as shown in FIG. 2, a shift between second speed and third speed is a clutch-to-clutch or synchronous shift, in which the clutch C0 is applied at substantially the same time the brake B1 is released, or vice versa. Similarly, a shift between third speed and fourth speed is a clutch-to-clutch shift in which the clutch C1 is applied at substantially the same time the brake B1 is released, or vice versa. In the above-mentioned hydraulic friction device, a line pressure regulated by a turbine torque T_T , i.e., an input torque T_{IN} of the automatic transmission 14, or a throttle opening amount θ_{TH} which is a value representative of the input torque T_{IN} , is used as the base pressure for the hydraulic friction devices.

[0016] FIG. 3 is a block diagram illustrating a control system provided in a vehicle, which controls the engine 10 and automatic transmission 14 and the like shown in FIG. 1. According to this control system, the operation amount (accelerator

opening amount) A_{CC} of an accelerator pedal 50 is detected by an accelerator operation amount sensor 51. This accelerator pedal 50 corresponds to an accelerator operating member and can be depressed to a large degree depending on the amount of output required by a driver. The accelerator pedal operation amount A_{CC} corresponds to the amount of required output. An electronic throttle valve 56 is provided in an intake pipe of the engine 10. A throttle actuator 54 changes the opening amount of this electronic throttle valve 56 so that it has an opening angle (opening amount) θ_{TH} (%) determined based on the accelerator pedal operation amount A_{CC} from a pre-stored (i.e., preset) relationship shown in FIG. 5. This relationship is set such that the throttle opening amount θ_{TH} increases as the accelerator pedal operation amount A_{CC} becomes larger. Also, in a bypass passage 52 which bypasses the electronic throttle valve 56 is provided an ISC (idle speed control) valve 53 that controls the intake air quantity when the electronic throttle valve 56 is fully closed in order to control an idle speed N_{EIDL} of the engine 10.

[0017] In addition, other sensors and switches are also provided, such as an engine speed sensor 58 for detecting an engine speed N_E of the engine 10, an intake air quantity sensor 60 for detecting an intake air quantity Q of the engine 10, an intake air temperature sensor 62 for detecting a temperature T_A of the intake air, a throttle sensor 64 with an idle switch for detecting when the electronic throttle valve 56 is fully closed (i.e., when the engine 10 is in an idle state) as well as for detecting the opening amount θ_{TH} of that electronic throttle valve 56, a vehicle speed sensor 66 for detecting a rotational speed N_{OUT} of the countershaft 44 which corresponds to the vehicle speed V , a coolant temperature sensor 68 for detecting a coolant temperature T_w of the engine 10, and a brake switch 70 for detecting whether a foot brake is being operated. In addition, other sensors and switches provided include a lever position sensor 74 for detecting a lever position (i.e., an operating position) P_{SH} of the shift lever 72, a turbine rotational speed sensor 76 for detecting a turbine rotational speed N_T (= rotational speed N_{IN} of the input shaft 22), an AT fluid sensor 78 for detecting an AT fluid temperature T_{OIL} , which is the temperature of the hydraulic fluid within the hydraulic pressure control circuit 98, a counter rotational speed sensor 80 for detecting a rotational speed N_C of the first counter gear G1, an ignition switch 82, and a knock sensor 84. Signals from these sensors indicative of the engine speed N_E , intake air quantity Q , intake air temperature T_A , throttle valve opening amount θ_{TH} , vehicle speed V , engine coolant temperature T_w , a brake operation, lever position P_{SH}

of the shift lever 72, turbine rotation speed N_T , AT fluid temperature T_{OIL} , counter rotational speed N_C , the operational position of the ignition switch 82, and knocking of the engine 10 and the like are supplied to an electronic control unit (ECU) 90. The brake switch 70 is an ON-OFF switch that switches the brake on or off depending on whether the brake pedal, which operates a main brake, is depressed or not.

[0018] The ECU 90 includes a microcomputer that has a CPU, RAM, ROM, an input/output interface and the like. The CPU controls the output of the engine 10 and the shifting of the automatic transmission 14 and the like by processing signals according to a program stored in the ROM beforehand while using the temporary storage function of the RAM. When necessary, the CPU may be configured such that a portion thereof for engine control is separate from a portion thereof for shift control. The output of the engine 10 is controlled by controlling the electronic throttle valve 56 open and closed with the throttle actuator 54, controlling a fuel injection valve 92 in order to control the fuel injection quantity, controlling an ignition device 94, such as an igniter, in order to control the ignition timing, and controlling the ISC valve 53 in order to control the idle speed. The electronic throttle valve 56 is controlled by, for example, driving the throttle actuator 54 based on the actual accelerator pedal operation amount A_{CC} according to the relationship between the accelerator pedal operation amount A_{CC} and the throttle valve opening amount θ_{TH} , shown in FIG. 5 for example, and increasing the throttle valve opening amount θ_{TH} as the accelerator pedal operation amount A_{CC} increases. When the engine 10 is started, the crankshaft 18 is cranked by a starter (i.e., an electric motor) 96. Further, in the shift control of the automatic transmission 14, the CPU 90 first determines the speed that the automatic transmission 14 should shift into from the current speed based on the actual throttle valve opening amount θ_{TH} and the vehicle speed V according to a pre-stored shift diagram (i.e., shift map), shown in FIG. 6, for example. The CPU 90 then outputs a shift command for starting a shift operation to shift the automatic transmission 14 from the current speed to the determined speed. The ECU 90 also switches solenoids S4 and SR of the hydraulic pressure control circuit 98 on (energized) and off (de-energized) and continually changes the energized state of the linear solenoid valves SL1, SL2, and SL3 and the like of the hydraulic pressure control circuit 98 by duty control or the like, so that shift shock due to a change in driving force or the like will not occur and the durability of the friction members will not be reduced. In FIG. 6, the solid lines are upshift lines and the broken lines are

downshift lines. The automatic transmission 14 shifts into a speed on the low speed side having a large gear ratio (= input rotational speed N_{IN} / output rotational speed N_{OUT}) as the vehicle speed V decreases or the throttle valve opening amount θ_{TH} increases. Denotations "1" through "5" in the drawing refer to the first speed "1st" through the fifth speed "5th".

[0019] FIG. 7 is a functional block diagram illustrating main portions of the hydraulic pressure control circuit 98 that are related to a 3 → 2 downshift. The hydraulic fluid pressure-fed from the hydraulic pump 88 is regulated by a first regulator valve 100, which is a relief valve, so as to become a first line hydraulic pressure P_{L1} . The hydraulic fluid flowing out through the first regulator valve 100 is then regulated by a second regulator valve 102, which is also a relief valve, so as to become a second line hydraulic pressure P_{L2} . The first line hydraulic pressure P_{L1} is supplied via a hydraulic line L1 to a manual valve 104 which is connected to the shift lever 72. When the shift lever 72 is shifted into either the D position (i.e., range) or the S position (i.e., range), a forward position pressure P_D which is equal to the first line hydraulic pressure P_{L1} is supplied from the manual valve 104 to each solenoid valve SL1, SL2, SL3, and the like, as well as to a shift valve, not shown. FIG. 7 shows the clutch C0 which is released to achieve the 3 → 2 downshift, the brake B1 which is applied to achieve the 3 → 2 downshift, the linear solenoid valve SL3 used to directly control the apply pressure P_{B1} of the brake B1, the linear solenoid valve SL2 used to directly control the apply pressure P_{C0} of the clutch C0, a hydraulic pressure sensor 106 connected to the brake B1 for detecting the apply pressure P_{B1} , a hydraulic pressure sensor 108 connected to the clutch C0 for detecting the apply pressure P_{C0} , a B1 clutch control valve 110 for regulating the apply pressure P_{B1} while the hydraulic fluid is being supplied, a C0 clutch control valve 112 for regulating the apply pressure P_{C0} while the hydraulic fluid is being supplied, a B1 accumulator 114 for reducing an increase in the apply pressure P_{B1} of the brake B1, and a C0 accumulator 116 for reducing an increase in the apply pressure P_{C0} of the clutch C0.

[0020] FIG. 8 is a functional block diagram illustrating a major part of a control function of the ECU 90, i.e., a shift control operation of the automatic transmission 14. FIG. 9 is a time chart illustrating a basic control operation for a clutch-to-clutch downshift of the automatic transmission 14. The state of the vehicle during this basic control operation is one in which a fuel cut operation (i.e., fuel supply to the engine 10 is cut off) by the fuel cut apparatus 118 that is executed when

the engine speed N_E is greater than a preset fuel cut lower limit speed (i.e., a fuel cut cancellation value C_F) when the accelerator pedal is not being depressed and the vehicle is decelerating, is in effect, such as when a clutch-to-clutch downshift control operation such as a $3 \rightarrow 2$ downshift is being performed, for example. Referring back to FIG. 8, rotational speed detecting means 120 detects the turbine rotational speed N_T (= rotational speed N_{IN} of the input shaft 22) from a signal from the turbine rotational speed sensor 76, for example, and also detects the engine speed N_E of the engine 10 from a signal from the engine speed sensor 58, for example. Inertia start determination means 130 determines (at time t_1) whether the turbine rotational speed N_T has started to increase following the shift to a low speed (e.g., second speed) during the downshift control operation while the vehicle is decelerating.

[0021] Shift state determining means 122 determines (at time t_0) whether a shift (i.e., hydraulic pressure control) of the automatic transmission 14 has started based on a signal output from the shift hydraulic pressure controlling means 124, which will be described later. The shift state determining means 122 then determines (at time t_2) whether the shift is complete based on whether or not the turbine rotational speed N_T substantially matches a rotational speed $\gamma_2 \times N_{OUT}$ calculated from the rotational speed N_{OUT} of the countershaft 44 detected by the vehicle speed sensor 66 and the gear ratio γ_2 of the speed (e.g., second speed) after the shift is complete. The shift state determining means 122 then determines (at time t_3) whether the shift hydraulic pressure control performed by the shift hydraulic pressure controlling means 124 has ended based on whether the apply pressure P_{B1} detected by the hydraulic pressure sensor 106 which is connected to the brake B1 has reached the maximum value such that the brake B1 is fully applied. Also, fuel cut controlling means 126 determines whether it is necessary to supply fuel to the engine 10 based on the engine speed N_E and the accelerator pedal operation amount A_{CC} and the like, and outputs a command to the fuel cut apparatus 118 to cut off the supply of fuel to the engine 10 depending on that determination. For example, when the vehicle is decelerating, during which the accelerator pedal operation amount A_{CC} is zero, but the engine speed N_E of the engine 10 is not below a predetermined value (i.e., a fuel cut cancellation value C_F), a fuel cut command is output so that a fuel cut is performed. When the engine speed N_E of the engine 10 slows to the predetermined value, the fuel cut command stops being output so that the fuel cut is stopped, i.e., the fuel cut is

cancelled. Fuel cut state determining means 128 determines whether the fuel cut has been cancelled based on a signal output to the fuel cut controlling means 126.

[0022] When the speed into which the automatic transmission 14 should be shifted from the current speed is determined based on the actual throttle valve opening θ_{TH} and the vehicle speed V from the shift diagram (i.e., the shift map) shown in FIG. 6, which is stored beforehand, for example, the shift hydraulic pressure controlling means 124 outputs a signal to the hydraulic pressure control circuit 98 to change the apply pressure of the hydraulic friction device so as to switch the automatic transmission 14 from the current speed to the other speed. For example, during the 3 \rightarrow 2 clutch-to-clutch downshift as shown in FIG. 9, an apply driving signal S_{PB1} is output to the linear solenoid valve SL3 which directly controls the apply pressure P_{B1} of the brake B1, which is a hydraulic friction device to be applied, and a release driving signal S_{PC0} is output to the linear solenoid valve SL2 which directly controls the apply pressure P_{C0} of the clutch C0, which is a hydraulic friction device to be released. The apply driving signal S_{PB1} will now be described. First, a signal S_{PB1W} is output to keep the apply pressure P_{B1} at a constant predetermined apply pressure P_{B1W} which is set lower than the pressure at which the brake B1 starts to be applied during the time t_{B1W} from the shift starting point t_0 . After the apply pressure P_{B1} is kept at the constant pressure, a signal is then output to smoothly increase it at a preset constant rate until it has been determined by the inertia start determining means 130 that inertia has started (time t_1). Next, a signal to smoothly change the apply pressure P_{B1} is output for feedback control so that the rotational speed N_{IN} of the input shaft (i.e., the turbine rotational speed N_T) smoothly increases at a predetermined constant rate from time t_1 until it has been determined by the shift state determining means 122 that the shift is complete (time t_2). A signal is then output to rapidly increase the apply pressure P_{B1} from time t_2 so as to fully apply the brake B1 (time t_3). Here, during time t_{B1A} from the start of the shift, a signal that is larger than the signal S_{PB1W} is output to quickly increase the apply pressure P_{B1} to the predetermined apply pressure P_{B1W} during time t_{B1W} .

[0023] Next, the release driving signal S_{PC0} will be described. First, a signal S_{PC0W} is output for keeping the apply pressure P_{C0} at a constant predetermined apply pressure (i.e., a holding pressure) P_{C0W} during time t_{C0W} . This predetermined apply pressure P_{C0W} is set lower than the maximum apply pressure, which is the first line hydraulic pressure P_{L1} , i.e., the base pressure before the start of the shift or the

originally supplied hydraulic pressure, and slightly higher than the pressure at which the clutch C0 starts to be released. After the apply pressure P_{C0} is kept at the constant pressure, a signal is then output to smoothly decrease (hereinafter, this smooth decrease is also referred to as “sweep”) it at a constant rate so as to fully release the clutch C0. Here, during time t_{C0A} after the start of the shift, a signal to fully release the clutch C0 is output to quickly decrease the apply pressure P_{C0} to the predetermined apply pressure P_{C0W} during time t_{C0W} after the start of the shift. The time t_{C0W} is a holding time for the holding pressure, during which the apply pressure P_{C0} is maintained at the constant predetermined pressure P_{C0W} . Because the time t_{C0W} is also the time from the start of the shift until the apply pressure P_{C0} starts to be smoothly changed (decreased), i.e., because the time t_{C0W} is also the time from the start of the shift until the apply pressure P_{C0} starts to be gradually decreased (i.e., until the start of sweep), time t_{C0W} also denotes the time until the start of sweep control (i.e., the time before starting to decrease the pressure).

[0024] Accordingly, when there is only a small degree of overlap between the application of the clutch C0 and the application of the brake B1, for example, when the time until the start of sweep control t_{C0W} is short, when, during the 3 → 2 clutch-to-clutch downshift while the vehicle is decelerating, the shift hydraulic pressure controlling means 124 decreases the apply pressure P_{C0} of the clutch C0, which is the hydraulic friction device to be released, while simultaneously increasing the apply pressure P_{B1} of the brake B1, which is the hydraulic friction device to be applied, there is a tendency for driving wheels (not shown) and the input shaft 22 become in a disconnected state, i.e., a neutral state, (hereafter referred to as “neutral tendency”) resulting in a momentary drop in both the turbine rotational speed N_T and the engine speed N_E (hereinafter referred to as “undershooting”; see FIG. 14). As a result, shift shock (a phenomenon resembling momentary engine brake) may occur when the engine speed N_E increases due to application of the brake B1 and the shift time may increase. Further, if the neutral tendency continues, the amount of undershooting of the engine speed N_E may increase to the extent that the fuel cut operation by the fuel cut controlling means 126 is cancelled, which may reduce the improvement in fuel efficiency achieved by the fuel cut. In contrast, when there is a large degree of overlap between the application of the clutch C0 and the application of the brake B1, for example, when the time until the start of sweep control t_{C0W} is long, the automatic transmission 14 may temporarily lock up and become in a tie-up state in

which the torque of the output shaft of the automatic transmission 14 suddenly decreases temporarily, resulting in shift shock and leading to degradation of the hydraulic friction devices of the automatic transmission 14. In this exemplary embodiment, the time until the start of sweep control t_{COW} is sequentially changed to the optimum value according to a repeated learning correction routine so that the neutral tendency and tie-up will not occur.

[0025] In this exemplary embodiment, lockup clutch slip controlling means, not shown, is also provided which outputs a driving signal S_{SLU} for the solenoid valve SLU that controls an apply pressure P_{LU} of the lockup clutch 32 in order to control a rotational speed difference N_{SLP} ($= N_E - N_T$) between the turbine rotational speed N_T and the engine speed N_E to a target rotational speed difference N_{SLP}^* . From time t_0 to time t_1 , the turbine rotational speed N_T and engine speed N_E gradually decrease as the vehicle decelerates, with the rotational speed difference N_{SLP} being made to substantially match the target rotational speed difference N_{SLP}^* , e.g., -50 rpm, by the driving signal S_{SLU} for the solenoid valve SLU. From time t_1 to time t_2 , the turbine rotational speed N_T starts to increase as the brake B1 is applied. The rate of this increase is controlled so as to be substantially constant by feedback control with the apply pressure P_{B1} of the brake B1. At this time, the driving signal S_{SLU} for the solenoid valve SLU is constant so the engine speed N_E increases along with the turbine rotational speed N_T , but for a slightly longer time. Further, from time t_2 to time t_3 , the turbine rotational speed N_T changes to a speed corresponding to the vehicle speed as the shift ends, and the rotational speed difference N_{SLP} is again made to substantially match the target rotational speed difference N_{SLP}^* , e.g., -50 rpm, by feedback control using the driving signal S_{SLU} for the solenoid valve SLU.

[0026] In the downshift control operation (see FIG. 14), undershooting amount calculating means 132 calculates an undershooting amount N_{US} of the turbine rotational speed N_T generated when there is little overlap between the application of the clutch C0 and the application of the brake B1, i.e., when the neutral tendency exists, according to the difference (i.e., $N_{US} = N_{TP} - N_T$) between an estimated turbine rotational speed N_{TP} ($= \gamma_3 \times N_{OUT}$) derived from the rotational output N_{OUT} of the countershaft 44 and the gear ratio γ_3 of the speed before the shift (e.g., third speed), and the actual turbine rotational speed N_T . A maximum undershooting amount N_{USMAX} is then obtained by consecutive comparisons with the size of this undershooting amount N_{US} . More specifically, the maximum undershooting amount

N_{USMAX} is calculated by first initializing (i.e., resetting) the value thereof to zero and then comparing the sizes of the maximum undershooting amount N_{USMAX} and the undershooting amount N_{US} . If the undershooting amount N_{US} is larger, that value replaces the maximum undershooting amount N_{USMAX} . The subsequent maximum undershooting amount N_{USMAX} and the undershooting amount N_{US} are compared again and the larger value is used as the maximum undershooting amount N_{USMAX} . Then undershooting amount determining means 134 determines whether the actual maximum undershooting amount N_{USMAX} is equal to, or greater than, a target undershooting amount N_{USU} , which is a first predetermined value, based on shift shock and the shift time and the like, or whether the actual maximum undershooting amount N_{USMAX} is equal to, or less than, an allowable undershooting amount N_{USD} , which is a second predetermined value lower than the first predetermined value, based on shift shock and the shift time and the like. The target undershooting amount N_{USU} is a so-called upper limit value for the region of the maximum undershooting amount N_{USMAX} which is to be the target. If the actual maximum undershooting amount N_{USMAX} exceeds this value, the neutral tendency increases. Also, the allowable undershooting amount N_{USD} is a so-called lower limit value for the region of the maximum undershooting amount N_{USMAX} which is to be the target. If the actual maximum undershooting amount N_{USMAX} falls below this value, there is a tendency for tie-up to occur.

[0027] Learning allowance determining means 136 determines whether a condition to start a learning correction routine is fulfilled in the learning correction routine at the time until the start of sweep control t_{cow} . For example, the learning allowance determining means 136 determines whether the AT fuel temperature T_{oil} and the coolant temperature T_w of the engine 10 and the like are stable, whether the various sensors, such as the AT fluid temperature sensor 78 and the coolant temperature sensor 68, or the turbine rotational speed sensor 76 and the like, are operating normally, and whether the shift is a single shift such as a 3 → 2 downshift. Memory state determining means 138 determines whether the learning correction routine was executed when EPROM such as EEPROM (electrically erasable programmable read-only memory) in which is stored, for example, a learning correction value L for the time until the start of sweep control t_{cow} , was in its initial state, or after its memory was initialized (i.e., cleared). The initial state of the

EEPROM is that of when it is either initially installed or replaced in the vehicle and the learning correction routine has not yet been performed.

[0028] Learning number updating means 140 updates a learning number n by adding 1 to the last learning number n stored in the EEPROM when the learning correction routine is executed during the time until the start of sweep control t_{c0w} , for example, and then stores that updated learning number n . Also, in the first learning correction routine when the EEPROM is in the initial state or after its memory has been initialized (i.e., cleared), the learning number n is updated so that $n = 0$ and that updated learning number n is then stored in memory. Learning number determining means 142 determines whether the normal learning routine may be executed by determining, for example, whether the learning number n of the learning correction routine for the time until the start of sweep control t_{c0w} exceeds a predetermined number n_c . This is because, although the time until the start of sweep control t_{c0w} is consecutively changed to the optimal value by repeating the learning correction routine, when the learning number n is small, dispersion in the maximum undershooting amount N_{USMAX} due to deviation among vehicles is unavoidable, so a learning correction routine different from the normal learning correction routine that is performed when the learning number n is large, for example, changing the coefficient to be multiplied by the maximum undershooting amount N_{USMAX} , is necessary in order to quickly reflect the learning correction value L in the next shift control operation. The predetermined number n_c is therefore set to 2 to 5, for example.

[0029] Learning controlling means 144 is provided with learning correction value calculating means 146 and sweep start time calculating means 148. The learning controlling means 144 sequentially changes the time until the start of sweep control t_{c0w} of the release driving signal S_{PC0} output to the linear solenoid valve SL2 that directly controls the apply pressure P_{C0} of the clutch C0, which is the hydraulic friction device to be released, to the optimal value by repeating the learning correction routine so that the turbine rotational speed N_T will not drop and tie-up will not occur. This learning controlling means 144 prevents the turbine rotational speed N_T from dropping and tie-up from occurring by keeping the apply driving signal S_{PB1} output to the linear solenoid valve SL3 that directly controls the apply pressure P_{B1} of the brake B1, which is the hydraulic friction device to be applied, constant each time

and executing the learning control routine only for the time until the start of sweep control t_{COW} of the release driving signal S_{PC0} .

[0030] When it is determined by the undershooting amount determining means 134 that the drop in the turbine rotational speed N_T is large, the learning correction value calculating means 146 calculates the learning correction value L according to the fuel cut state determined by the fuel cut state determining means 128 in order to avoid the neutral tendency. If the fuel cut is still in effect, a new learning correction value $L_{NCUT} (= L_C + G \times N_{USMAX})$ is obtained by adding the product of the maximum undershooting amount N_{USMAX} and a coefficient G (gain) to the current learning correction value L_C . The gain G is a value determined beforehand in order to reflect the maximum undershooting amount N_{USMAX} in the new learning correction value L_{NCUT} . The gain G becomes a normal learning gain G_F if the learning number n exceeds the predetermined number n_C , and becomes a high speed learning gain G_K if the learning number does not exceed the predetermined number n_C . The high speed learning gain G_K is a value larger than the normal learning gain G_F so that the learning correction value L is quickly reflected in the next shift control operation. Also, because the time until the start of sweep control t_{COW} when the fuel cut has been cancelled is shorter than it is during normal learning, the apply pressure P_{C0} of the clutch $C0$, which is the hydraulic friction device to be released, is quickly reduced so the neutral tendency exists for longer and an undershooting amount N_{EUS} of the engine speed N_E becomes larger. Accordingly, for the purpose of improving fuel efficiency and the like as well, it is necessary to make the undershooting amount N_{EUS} an amount in which the fuel cut will not be cancelled in the fewest number of times possible. Therefore, instead of calculating using the normal learning, a new learning correction value $L_{NCAN} (= L_C + L_{NE})$ is obtained by adding a learning correction value for emergency neutral avoidance learning L_{NE} to the current learning correction value L_C . The value of the maximum undershooting amount N_{USMAX} calculated from the undershooting amount N_{US} will not be a correct maximum value because the fuel cut has been cancelled and the engine speed N_E has increased. Therefore, a predetermined value, not the product of the maximum undershooting amount N_{USMAX} and the gain G used during normal learning and the like, is used as the value of the learning correction value for emergency neutral avoidance learning L_{NE} .

[0031] When the undershooting amount determining means 134 determines that there is a tie-up tendency, as well as determines whether the

maximum undershooting amount N_{USMAX} is equal to, or less than, a preset zero determination value in which factors such as noise from, and the precision of, the apparatus have been appropriately considered, i.e., determines whether the maximum undershooting amount N_{USMAX} is a small value substantially equal to zero, the learning correction value calculating means 146 calculates the learning correction value L in order to avoid tie-up. When the maximum undershooting amount N_{USMAX} is not equal to, or less than, the zero determination value, the undershooting amount N_{US} or N_{EUS} of the turbine rotational speed N_T or the engine speed N_E are generated to some extent, but the state of the automatic transmission 14 is close to tie-up so a new learning correction value L_{TU} ($= L_C - L_{TF}$) is obtained by subtracting a learning correction value for normal learning L_{TF} from the current learning correction value L_C so as to shorten the time until the start of sweep control t_{COW} in order to quickly reduce the apply pressure P_{C0} of the clutch C0, which is the hydraulic friction device to be released. When the maximum undershooting amount N_{USMAX} is equal to, or less than, the zero determination value, the automatic transmission 14 is in the tie-up state so a new learning correction value L_{TT} ($= L_C - L_{TE}$) is obtained by subtracting a learning correction value for emergency tie-up avoidance learning L_{TE} from the current learning correction value L_C so that the time until the start of sweep control t_{COW} becomes shorter than that for normal learning with one execution of the learning correction routine in order to quickly avoid shift shock. A predetermined value is used for the learning correction value for normal learning L_{TF} or the learning correction value for emergency tie-up avoidance learning L_{TE} .

[0032] The sweep start time calculating means 148 calculates a next time until the start of sweep control t_{CNEXT} ($= t_{COC} + L_{NEW}$) of the apply pressure P_{C0} of the clutch C0 by adding a new learning correction value L_{NEW} (L_{NCUT} , L_{NCAN} , L_{TU} or L_{TT}) obtained by the learning correction value calculating means 146 to the current time until the start of sweep control t_{COC} . The new learning correction value L_{NEW} is calculated by the learning correction value calculating means 146 such that $L_{NCAN} > L_{NCUT} > 0$ in order to increase the current time until the start of sweep control t_{COC} when there is a neutral tendency, and such that $L_{TT} < L_{TU} < 0$ in order to reduce the current time until the start of sweep control t_{COC} when there is a tie-up tendency.

[0033] FIG. 10 is a flowchart illustrating a main routine for explaining the learning correction routine of the time until the start of sweep control t_{COW} of the release driving signal S_{PC0} output to the linear solenoid valve SL2 which directly

controls the apply pressure P_{C0} of the clutch C0, which is the hydraulic friction device to be released, in a major part of the control operation of the ECU 90, i.e., in the shift control operation of the automatic transmission 14 during a clutch-to-clutch downshift while decelerating. FIG. 11 is a flowchart of a learning correction value calculating routine which is a subroutine in the routine shown in FIG. 10. FIG. 12 is a flowchart of a neutral avoidance learning routine which is a subroutine in the routine shown in FIG. 11. FIG. 13 is a flowchart of a tie-up avoidance learning routine which is a subroutine in the routine shown in FIG. 11.

[0034] Referring to FIG. 10, steps S1 and S2 correspond to the memory state determining means 138. In step S1 it is determined whether EPROM, such as EEPROM (electrically erasable programmable read-only memory), in which is stored the learning correction value L and the like, has just been installed in the vehicle and is in a state in which the learning correction routine has not yet been executed, or whether EEPROM which has just been replaced is in a state in which the learning correction routine has not yet been executed. In step S2, it is determined whether the learning correction routine has been executed after the EEPROM has been initialized (i.e., cleared). If the determination in step S1 or step S2 is YES, the process proceeds on to step S3, which corresponds to the learning number updating means 140, in which the learning number n is updated so that $n = 0$, and that value is stored in the EEPROM. If the determination in both steps S1 and S2 is NO, step S3 is not executed and the value of the learning number n stored in the EEPROM is maintained.

[0035] Next, in step S4, which corresponds to the shift state determining means 122, it is determined whether the shift (i.e., hydraulic pressure control) of the automatic transmission 14 has started. If the determination in step S4 is NO, the routine ends. If the determination is YES, however, the value of the maximum undershooting amount N_{USMAX} is set to $N_{USMAX} = 0$ in step S5, which corresponds to the undershooting amount calculating means 132. Steps S6 and S7 both correspond to the undershooting amount calculating means 132. In step S6, first, the current undershooting amount N_{USC} is derived from the difference ($N_{US} = N_{TP} - N_T$) between the rotational speed $\gamma_3 \times N_{OUT}$ (i.e., the estimated turbine rotational speed N_{TP}) calculated from the rotational speed N_{OUT} of the countershaft 44 and the gear ratio γ_3 of the speed before the shift (e.g., third speed), and the actual turbine rotational speed N_T . Then, it is determined whether the current undershooting amount N_{USC} is greater

than the maximum undershooting amount N_{USMAX} . If the determination in step S6 is YES, then in step S7 the current undershooting amount N_{USC} is made the maximum undershooting amount N_{USMAX} and the memory of the maximum undershooting amount N_{USMAX} is updated.

5 **[0036]** Next, in step S8, which corresponds to the inertia start determining means 130, it is determined whether the turbine rotational speed N_T has started to increase. Step S6 is repeatedly executed until the determination in step S8 is YES. Only when the determination in step S6 is YES is the current undershooting amount N_{USC} made the maximum undershooting amount N_{USMAX} and the memory of the maximum undershooting amount N_{USMAX} sequentially updated in step S7. That is, in 10 steps S5 to S8, even if the value of the maximum undershooting amount N_{USMAX} is determined and the automatic transmission 14 is in a tie-up state in which undershooting will not occur, the maximum undershooting amount N_{USMAX} is determined so as to equal 0. If the determination in step S8 is YES, it is determined in 15 step S9, which corresponds to the shift state determining means 122, whether the apply pressure P_{B1} detected by the hydraulic pressure sensor 106 that is connected to the brake B1, which is the hydraulic friction device to be applied, has reached the maximum value so that the brake B1 is fully applied, and the shift hydraulic pressure control has ended. Step S9 is repeatedly executed until the determination is YES, i.e., 20 until the shift hydraulic pressure control has ended.

[0037] Next, in steps SG1 to SG7 in FIG. 11, which correspond to step S10 in FIG. 10, the new learning correction value L_{NEW} (L_{NCUT} , L_{NCAN} , L_{TU} or L_{TT}) to be added to the current time until the start of sweep control t_{COC} (t_{COCOT} , t_{COCAN} or t_{COT}) of the clutch C0, which is the hydraulic friction device to be released, is obtained and the 25 next time until the start of sweep control t_{CONEXT} (t_{CONG} , t_{CONE} or t_{CONT} , $= t_{COC} + L_{NEW}$) of the apply pressure P_{C0} of the clutch C0 is calculated. In step SG1, which corresponds to the learning allowance determining means 136, it is determined whether a condition to start the learning correction routine has been fulfilled. That determination is made based, for example, on whether the AT fuel temperature T_{OIL} 30 and the coolant temperature T_w of the engine 10 and the like are stable, whether various sensors such as the AT fluid temperature sensor 78 and the coolant temperature sensor 68, or the turbine rotational speed sensor 76 and the like, are operating normally, and whether the shift is a single shift such as a 3 → 2 downshift. If the determination in step SG1 is NO, the routine ends.

[0038] If the determination in step SG1 is YES, then it is determined in step SG2, which corresponds to the undershooting amount determining means 134, whether the maximum undershooting amount N_{USMAX} determined in steps S5 to S8 is equal to, or greater than, the target undershooting amount N_{USU} . If the determination in step SG2 is NO, it is determined in step SG3, which also corresponds to the undershooting amount determining means 134, whether the maximum undershooting amount N_{USMAX} is equal to, or less than, the allowable undershooting amount N_{UDS} . If the determination in either step SG2 or step SG3 is NO, the routine ends. That is, if the maximum undershooting amount N_{USMAX} is between the target undershooting amount N_{USU} , which is the upper limit of the maximum undershooting amount N_{USMAX} , and the allowable undershooting amount N_{USD} , which is the lower limit of the maximum undershooting amount N_{USMAX} , there is no need to execute the learning correction routine so the routine ends. If the determination in step SG2 is YES, the new learning correction value L_{NEW} (L_{NCUT} or L_{NCAN}) to be added to the current time until the start of sweep control t_{COC} (t_{COCOT} or t_{COCAN}) of the clutch C0 in order to avoid the neutral tendency is obtained in steps SN1 to SN6 in FIG. 12, which correspond to step SG4 in FIG. 11. If the determination in step SG3 is YES, the new learning correction value L_{NEW} (L_{TU} or L_{TT}) to be added to the current time until the start of sweep control t_{COC} (t_{COT}) of the clutch C0 in order to avoid tie-up is obtained in steps ST1 to ST3 in FIG. 13, which correspond to step SG5 in FIG. 11.

[0039] In step SN1, which corresponds to the fuel cut state determining means 128, it is determined whether a command to cut off the fuel supply to the engine 10 which is output to the fuel cut apparatus 118 by the fuel cut controlling means 126 during the downshift control operation while the vehicle is decelerating has been cancelled. In step SN2, which corresponds to the learning number determining means 142, it is determined whether the learning number n of the learning correction routine for the time until the start of sweep control stored in the EEPROM is exceeding the predetermined number n_c , for example, 2 to 5. Then, in steps SN3 to SN6, which correspond to the learning correction value calculating means 146, the learning correction value for avoiding the neutral tendency according to the results of steps SN1 and SN2 is calculated. That is, if the determination in step SN1 is NO and the determination in step SN2 is YES, the normal learning gain G_F is made the gain in step SN3 for the normal learning routine. Then in step SN6, a new learning correction value L_{NCUT} ($= L_C + G_F \times N_{USMAX}$) is calculated by adding the

product of the normal learning gain G_F and the maximum undershooting amount N_{USMAX} to the current learning correction value L_C .

[0040] Further, if the determinations in both steps SN1 and SN2 are NO, because the dispersion in the maximum undershooting amount N_{USMAX} due to deviation among vehicles from the learning number n being low is unavoidable, the high speed learning gain G_K , which is a value larger than the normal learning gain G_F , is made the gain in step SN4 so that the learning correction value L is quickly reflected in the next shift control operation, and in step SN6, the product of the high speed gain G_K and the maximum undershooting amount N_{USMAX} is added to the current learning correction value L_C to obtain the new learning correction value L_{NCUT} ($= L_C + G_K \times N_{USMAX}$). Also, if the determination in step SN1 is YES, because the fuel cut is cancelled due to the fact that the undershooting amount N_{EUS} of the engine 10 is large, as well as in order to improve fuel efficiency and the like, an undershooting amount N_{US} (N_{EUS}) which does not cancel the fuel cut is necessary in the fewest number of times possible. Therefore, in step SN5, the new learning correction value L_{NCAN} ($L_{NCAN} = L_C + L_{NE}$) is obtained by adding the learning correction value for emergency neutral avoidance learning L_{NE} to the current learning correction value L_C . The value of the maximum undershooting amount N_{USMAX} derived from the undershooting amount N_{US} will not be the correct maximum value because the fuel cut has been cancelled and the engine speed N_E has increased. Therefore, a predetermined value, not the product of the maximum undershooting amount N_{USMAX} and the gain G used during normal learning and the like, is used as the value of the learning correction value for emergency neutral avoidance learning L_{NE} .

[0041] In step ST1, which corresponds to the undershooting amount determining means 134, it is determined whether the maximum undershooting amount N_{USMAX} is equal to, or less than, the zero determination value. If the determination in step ST1 is NO, the undershooting amount N_{US} or N_{EUS} of the turbine rotational speed N_T or the engine speed N_E is generated to some extent, but the state of the automatic transmission 14 is close to tie-up so the new learning correction value L_{TU} ($= L_C - L_{TF}$) is obtained by subtracting the learning correction value for normal learning L_{TF} from the current learning correction value L_C so as to shorten the current time until the start of sweep control t_{COC} (t_{COT}) of the clutch C0. If the determination in step SN1 is YES, the automatic transmission 14 is in the tie-up state so the new learning correction value L_{TT} ($= L_C - L_{TE}$) is obtained by subtracting the learning correction value for

emergency tie-up avoidance learning L_{TE} from the current learning correction value L_C so that the current time until the start of sweep control t_{COC} (t_{COT}) becomes shorter than that for normal learning with one execution of the learning correction routine in order to quickly avoid shift shock. A predetermined value is used for the learning correction value for normal learning L_{TF} or the learning correction value for emergency tie-up avoidance learning L_{TE} .

[0042] When the new learning correction value L_{NEW} (L_{NCUT} , L_{NCAN} , L_{TU} or L_{TT}) is obtained in step SG4 (i.e., steps SN1 to SN6) or step SG5 (i.e., steps ST1 to ST3), the learning number n is updated in step SG6, which corresponds to the learning number updating means 140, by adding 1 to the last learning number n stored in the EEPROM, and that value is stored in the EEPROM.

[0043] Next, in step SG7, which corresponds to the sweep start time calculating means 148, the next time until the start of sweep control t_{CONEXT} (t_{CONG} , t_{CONE} or t_{CONT} , $= t_{COC} + L_{NEW}$) of the apply pressure P_{C0} of the clutch C0 is calculated by adding the new learning correction value L_{NEW} (L_{NCUT} , L_{NCAN} , L_{TU} or L_{TT}) obtained by the learning correction value calculating means 146 to the current time until the start of sweep control t_{COC} (t_{COCUT} , t_{COCAN} or t_{COT}). The new learning correction value L_{NEW} is calculated in step SG4 (i.e., steps SN1 to SN6) or step SG5 (i.e., steps ST1 to ST3) such that $L_{NCAN} > L_{NCUT} > 0$ in order to increase the current time until the start of sweep control t_{COC} when there is a neutral tendency, and such that $L_{TT} < L_{TU} < 0$ in order to reduce the current time until the start of sweep control t_{COC} when there is a tie-up tendency.

[0044] FIG. 14 is a time chart illustrating a case in which the normal learning routine or the high speed learning routine for the neutral tendency is executed in the shift control operation of the automatic transmission 14 during a downshift while the vehicle is decelerating, according to the exemplary embodiment. In the drawing, the solid lines denote values before execution of the learning routine and the broken lines denote values after execution of the learning routine. As illustrated in the drawing, after execution of the learning routine, the time until the start of sweep control is increased from t_{COCUT} (the current time until the start of sweep control t_{COC}) to t_{CONG} (the next time until the start of sweep control t_{CONEXT} of the apply pressure P_{C0} of the clutch C0). As a result, an undershoot U from insufficient apply pressure P_{C0} by the clutch C0, which is the hydraulic friction device to be released, is reduced. Therefore, shift shock (a phenomenon resembling momentary engine brake) when the

engine speed N_E increases due to application of the brake B1 is reduced. Also, the increase in the turbine rotational speed N_T is started earlier (inertia start, time t_{ING}), and as a result, the shift control (hydraulic pressure control) ends sooner, at time t_{3NG} instead of time t_{3N} . This is substantially the same amount of time as the time from the inertia start until the end of the hydraulic pressure control, so if the inertia start is moved back (i.e., started earlier), the hydraulic pressure control will end earlier. Also, the only difference in the expression for obtaining the new learning correction value $L_{NCUT} (= L_C + G \times N_{USMAX})$ for the normal learning routine and the high speed learning routine is that the gain G is made either the normal learning gain G_F or the high speed learning gain G_K depending on the learning number n . Therefore, except for the fact that the difference between the time until the start of sweep control after learning and the time until the start of sweep control before learning (i.e., $t_{CONG} - t_{COCUT}$) is greater with the high speed learning routine, the normal learning routine and the high speed learning routine are the same.

[0045] FIG. 15 is a time chart illustrating a case in which the emergency learning routine for the neutral tendency is executed in the shift control operation of the automatic transmission 14 during a downshift while the vehicle is decelerating, according to the exemplary embodiment. In the drawing, the solid lines denote values before execution of the learning routine and the broken lines denote values after execution of the learning routine. From the drawings, it is evident that the only substantial difference between the cases shown in FIG. 14 and FIG. 15 is that, before execution of the learning routine, the engine speed N_E drops to the fuel cut cancellation value C_F in FIG. 15 because the undershoot U_K in FIG. 15 is greater than the undershoot U in FIG. 14, and as a result, the fuel cut is canceled (time t_{CF}). After the learning routine, the time until the start of sweep control is increased from t_{COCAN} (the current time until the start of sweep control t_{COC}) to t_{CONE} (the next time until the start of sweep control t_{CONEXT} of the apply pressure P_{C0} of the clutch C0). As a result, the undershoot U_K from insufficient apply pressure P_{C0} by the clutch C0, which is the hydraulic friction device to be released, is reduced. Also, the increase in the turbine rotational speed N_T is started earlier (inertia start, time t_{INE}), and as a result, the shift control (i.e., hydraulic pressure control) ends sooner, at time t_{3NE} instead of time t_{3E} . Further, fuel efficiency is improved because the fuel cut is continued.

[0046] FIG. 16 is a time chart illustrating a case in which the emergency learning routine for tie-up is executed in the shift control operation of the automatic

transmission 14 during a downshift while the vehicle is decelerating, according to the exemplary embodiment. In the drawing, the solid lines denote values before execution of the learning routine and the broken lines denote values after execution of the learning routine. As can be seen in the drawing, after execution of the learning routine, the time until the start of sweep control is decreased from t_{COT} (the current time until the start of sweep control t_{COC}) to t_{CONT} (the next time until the start of sweep control t_{CONEXT} of the apply pressure P_{C0} of the clutch C0). As a result, the apply pressure P_{C0} of the clutch C0, which is the hydraulic friction device to be released, decreases sooner, thus reducing the degree of overlap between the application of the clutch C0 and the application of the brake B1. As a result, shift shock due to lockup, i.e., tie-up, of the automatic transmission 14 is reduced. Further, the increase in the turbine rotational speed N_T is started earlier (inertia start, time t_{INT}), and as a result, the shift control (i.e., hydraulic pressure control) ends sooner, at time t_{3NT} instead of time t_{3T} . Also, the normal learning routine and the emergency learning routine are substantially the same except for i) the fact that the difference between the time until the start of sweep control before learning and the time until the start of sweep control after learning (i.e., $t_{COT} - t_{CONT}$), which differs depending on whether, in the expression for obtaining the new learning correction value L_{NEW} ($= L_{TU}, L_{TT}$), the new learning correction value L_{TU} ($= L_C - L_{TF}$) derived by subtracting the learning correction value for normal learning L_{TF} from the current learning correction value L_C , or the new learning correction value L_{TT} ($= L_C - L_{TE}$) derived by subtracting the learning correction value for emergency tie-up avoidance learning L_{TE} from the current learning correction value L_C is calculated, is larger with the emergency learning routine, and ii) the fact that, with the normal learning routine, the automatic transmission 14 is close to being in a tie-up state such that an undershoot is generated.

[0047] Accordingly, in the exemplary embodiment, the learning controlling means 144 (step S10) corrects, through learning control, the apply pressure of at least one of the hydraulic friction devices operated for the clutch-to-clutch downshift so as to increase the amount of drop (i.e., the undershooting amount N_{US}) in the rotational speed N_{IN} of the input shaft when the degree of overlap between the release of the hydraulic friction device to be released (i.e., the clutch C0) and the application of the hydraulic friction device to be applied (i.e., the brake B1) is large and the amount of drop (i.e., the maximum undershooting amount N_{USMAX}) in the rotational speed N_{IN} of the input shaft (i.e., the turbine rotational speed N_T) of the

automatic transmission 14 is less than the predetermined value (i.e., the allowable undershooting amount N_{USD}) during a clutch-to-clutch downshift while decelerating. As a result, shift shock due to a large degree of overlap between the release of the hydraulic friction device to be released and the application of the hydraulic friction device to be applied during a clutch-to-clutch downshift while decelerating is appropriately reduced or eliminated.

[0048] Also according to the exemplary embodiment, when a command for the clutch-to-clutch downshift is output, the shift hydraulic pressure controlling means 124 maintains the apply pressure P_{C0} of the hydraulic friction device to be released (i.e., the clutch C0) for the predetermined holding time t_{COW} at the predetermined holding pressure P_{COW} which is set lower than the base pressure of the apply pressure P_{C0} and higher than the pressure at which the hydraulic friction device to be released starts to release. The shift hydraulic pressure controlling means 124 then smoothly decreases the apply pressure P_{C0} of the hydraulic friction device to be released (i.e., the clutch C0) at a constant rate, while increasing the apply pressure P_{B1} of the hydraulic friction device to be applied (i.e., the brake B1) so that the rotational speed N_{IN} of the input shaft (i.e., the turbine rotational speed N_T) smoothly increases at a constant rate. As a result, the clutch-to-clutch downshift is able to be appropriately executed.

[0049] Also according to the exemplary embodiment, when the amount of drop (i.e., the maximum undershooting amount N_{USMAX}) in the rotational speed N_{IN} of the input shaft (i.e., the turbine rotational speed N_T) is less than the predetermined value (i.e., the allowable undershooting amount N_{USD}), the learning controlling means 144 (step S10) corrects the holding time t_{COW} of the holding pressure (i.e., the current time until the start of sweep control t_{COC}) of the hydraulic friction device to be released (i.e., the clutch C0) through learning so that it becomes shorter. As a result, the amount of drop N_{US} in the rotational speed N_{IN} of the input shaft is increased.

[0050] Also according to the exemplary embodiment, when the amount of drop (i.e., the maximum undershooting amount N_{USMAX}) in the rotational speed N_{IN} of the input shaft (i.e., the turbine rotational speed N_T) of the automatic transmission 14 is less than the predetermined value (i.e., the allowable undershooting amount N_{USD}), the learning controlling means 144 (step S10) corrects, so as to advance, the time at which to start decreasing pressure t_{CONEXT} ($t_{CONEXT} = t_{COC} + L_{NEW}$) from the holding pressure P_{COW} of the hydraulic friction device to be released in the next clutch-to-

clutch downshift through learning by adding (actually, subtracting, by making L_{TU} or L_{TT} a negative number) the learning correction value L_{NEW} (L_{TU} or L_{TT}) to the time at which to start decreasing pressure (i.e., the current time until the start of sweep control t_{COC} (t_{COT})) from the holding pressure P_{COW} of the hydraulic friction device to be released (i.e., the clutch C0) during in the last clutch-to-clutch downshift. As a result, the amount of drop N_{US} in the rotational speed N_{IN} of the input shaft increases.

[0051] Also according to the exemplary embodiment, when the amount of drop (i.e., the maximum undershooting amount N_{USMAX}) in the rotational speed N_{IN} of the input shaft (i.e., the turbine rotational speed N_T) of the automatic transmission 14 is less than the predetermined value (i.e., the allowable undershooting amount N_{USD}), the learning controlling means 144 (step S10) corrects the holding time of the holding pressure (i.e., the current time until the start of sweep control t_{COC} (t_{COT})) of the hydraulic friction device to be released through learning to be shorter when the amount of drop (i.e., the maximum undershooting amount N_{USMAX}) is equal to, or less than, the zero determination value for determining that the amount of drop N_{USMAX} is a small value such as zero or therearound than when the amount of drop (i.e., the maximum undershooting amount N_{USMAX}) is not equal to, or less than, the zero determination value, by using a larger learning correction value L_{TT} . As a result, the amount of increase in the amount of drop N_{US} with one execution of learning control is larger so the amount of drop N_{US} in the rotational speed N_{IN} of the input shaft is quickly increased.

[0052] Although the invention has been described in detail in terms of exemplary embodiments with reference to the drawings, the invention is not limited to those exemplary embodiments.

[0053] For example, in the foregoing exemplary embodiment, the clutch-to-clutch downshift operation of the automatic transmission 14 during deceleration of the vehicle is performed with a $3 \rightarrow 2$ downshift. Alternatively, however, the operation may also be performed with a $5 \rightarrow 4$, $4 \rightarrow 3$, $2 \rightarrow 1$ or other downshift.

[0054] Also, in the exemplary embodiment, the automatic transmission 14 is a FF transverse-mounted transmission with five forward speeds which is constructed of a combination of three planetary gearsets 40, 42, and 46. Alternatively, however, the number of planetary gearsets which in combination make up the automatic transmission 14 may be a number other than three. The automatic

transmission 14 may also be a longitudinal-mounted transmission for a FR (front engine, rear drive) vehicle, or the like.

[0055] Also in the exemplary embodiment, the learning control means 144 corrects the time at which to start decreasing pressure (i.e., the current time until the start of sweep control t_{COC} (t_{COT})) from the predetermined apply pressure P_{COW} of the clutch C0, which is the hydraulic friction device to be released, through learning so that it is advanced, and increases the undershoot amount N_{US} so as to avoid the tie-up tendency. Alternatively, however, the tie-up tendency can also be avoided by correcting the predetermined apply pressure P_{COW} through learning so that it decreases, thus advancing the time at which the clutch C0 is released and increasing the undershoot amount N_{US} . Also, the tie-up tendency can also be avoided by increasing the undershoot amount N_{US} by applying the brake B1 later by having the learning controlling means 144 correct, through learning, the time at which to start increasing pressure (i.e., the time during which the apply pressure P_{BIW} is maintained after the start of the shift) from the predetermined apply pressure P_{BIW} that is set lower than the pressure at which the apply pressure P_{BI} of the brake B1, which is the hydraulic friction device to be applied, starts to be applied, so as to delay that time at which to start increasing pressure (i.e., increase the time during which the apply pressure P_{BIW} is maintained after the start of the shift), or correct the predetermined apply pressure P_{BIW} so as to make it smaller.

[0056] While the invention has been described with reference to exemplary embodiments thereof, it is to be understood that the invention is not limited to the exemplary embodiments or constructions. To the contrary, the invention is intended to cover various modifications and equivalent arrangements. In addition, while the various elements of the exemplary embodiments are shown in various combinations and configurations, which are exemplary, other combinations and configurations, including more, less or only a single element, are also within the spirit and scope of the invention.